


Loop control



application areas

Printing and Paper

Logistics

Packaging

In this case an ultrasonic sensor with analogue output scans from above into the loop and adjusts the material feed depending on the depth of the loop.

If a loop of material tends to swing sideways, the sound waves are very easily deflected away when scanning from above. In such cases it is recommended to scan the loop from below, as shown in the diagram.

Depending on the width of the web material and the measurement range, two sensor families with different housing designs are available:

- **mic+ with M30 threaded sleeve:** Measuring range of 350 mm or 1,300 mm
- **lcs with cubic housing:** Measuring range of 350 mm or 1,300 mm

SENSORS FOR THIS APPLICATION AREA



mic+35/IU/TC

operating range: 65 - 600 mm

housing: cylindrical M30

outputs: 1 x analogue 4-20 mA + 0-10 V



lcs-35/IU/QP

operating range: 65 - 600 mm

housing: cuboidal

outputs: 1 x analogue 4-20 mA + 0-10 V



mic+130/IU/TC

operating range: 200 - 2.000 mm

housing: cylindrical M30

outputs: 1 x analogue 4-20 mA + 0-10 V



lcs-130/IU/QP

operating range: 200 - 2.000 mm

housing: cuboidal

outputs: 1 x analogue 4-20 mA + 0-10 V