




extract from our online catalogue:

dbk-4/Empf/CEE/O/QP

current to: 2026-09-22

dbk-4/Empf/CEE/O/QP

Successor model available

please inquire



design	cuboidal
operating mode	double sheet control
working range	papers with weights of 20 - 800 g/m ² , metal-laminated sheets and films up to 0.25 mm thick, self-adhesive films
particularities	receiver for ultrasonic double sheet control cuboidal lateral sound exit

Ultrasonic-Specific

means of measurement	pulse operation with amplitude evaluation
transducer frequency	400 kHz
blind zone	7 mm in front of transmitter and receiver

Electrical Data

operating voltage U_B	20 - 30 V d.c., reverse polarity protection
voltage ripple	± 10 %
no-load current consumption	≤ 45 mA
type of connection	2 m PVC cable, 5 × 0.25 mm ²

outputs

output 1	double sheet output npn: $I_{\max} = 500 \text{ mA}$ ($-U_B+2V$) NCC, short-circuit-proof
Ausgang 2	missing sheet output npn: $I_{\max} = 500 \text{ mA}$ ($-U_B+2V$) NCC, short-circuit-proof
response delay	2.5 ms or 6.5 ms in free-run mode

Inputs

input 1	control input
---------	---------------

housing

material	brass sleeve, nickel-plated, plastic parts, PBT
ultrasonic transducer	polyurethane foam, epoxy resin with glass contents
class of protection to EN 60529	IP 65
operating temperature	+5°C to +60°C
storage temperature	-40°C to +85°C
weight	

Technical Features/Characteristics

controls	not necessary
scope for settings	not necessary
indicators	1 x Duo-LED; green: working / red: double sheet / flashing red: missing sheet

pin assignment

