




extract from our online catalogue:

vnp-130/IU/TC


current to: 2026-09-03

vnp-130/IU/TC

scale drawing



detection zone



Successor model available

please inquire

 1 x analogue 4-20 mA + 0-10 V

 2,000 mm

design

cylindrical M30

operating mode

analogue distance measurements

particularities

virtual zero settable
display

Ultrasonic-Specific

means of measurement

echo propagation time measurement

transducer frequency

200 kHz

blind zone

200 mm

operating range

1,300 mm

max. range

2,000 mm

resolution

0.18 mm to 0.57 mm, depending on the analogue window

reproducibility

± 0.15 %

accuracy

± 1 % (temperature drift internally compensated)

Electrical Data

operating voltage U_B

9 - 30 V d.c., reverse polarity protection

voltage ripple

± 10 %

no-load current consumption

≤ 80 mA

type of connection

5-pin M12 initiator plug

outputs

output 1

analogue output
current: 4-20 mA / voltage: 0-10 V (at $U_B \geq 15$ V), short-circuit-proof
switchable rising/falling

response delay

110 ms

delay prior to availability

< 300 ms

Inputs

input 1	com input synchronisation input teach-in input
---------	--

housing

material	brass sleeve, nickel-plated, plastic parts, PBT, TPU
ultrasonic transducer	polyurethane foam, epoxy resin with glass contents
class of protection to EN 60529	IP 67
operating temperature	-25°C to +70°C
storage temperature	-40°C to +85°C
weight	110 g

Technical Features/Characteristics

temperature compensation	yes
controls	2 push-buttons + LED display (TouchControl) com input
scope for settings	Teach-in and numeric configuration via TouchControl LCA-2 with LinkControl
synchronization	yes
multiplex	yes
indicators	3-digit LED display, 2 x three-colour LED

Accessories

deployable accessory	KST5A-2/M12 KST5A-5/M12 KST5G-2/M12 KST5G-5/M12 BF-30 UF-90/M30 LCA-2
----------------------	---

pin assignment

