microsonic



extract from our online catalogue:

Trans-O-Prox II


current to: 2026-09-22

microsonic GmbH / Phoenixseestraße 7 / 44263 Dortmund / Germany / **T** +49 231 975151-0 / **F** +49 231 975151-51 / **E** info@microsonic.de
microsonic® ist eine eingetragene Marke der microsonic GmbH. Alle Rechte vorbehalten. Änderungen vorbehalten.

Archivsensor

Trans-O-Prox II

scale drawing



Successor model available	please inquire

2 x pnp

design	cuboidal
operating mode	evaluator
particularities	archive sensor

Ultrasonic-Specific

means of measurement	echo propagation time measurement
resolution	5 cm

Electrical Data

operating voltage U_B	24 V d.c., reverse polarity protection
voltage ripple	± 10 %
no-load current consumption	≤ 50 mA (without sensors)
type of connection	screw terminals, wire cross-section 1.5 mm^2

outputs

output 1	switching output pnp: I_{max} = 500 mA (U_B-2V) NOC/NCC adjustable, short-circuit-proof
Ausgang 2	switching output pnp: I_{max} = 500 mA (U_B-2V) NOC/NCC adjustable, short-circuit-proof
response delay	transponder mode: 500 ms, echo mode: 240 ms

Inputs

input 1	com input
Eingang 2	enable-input
Eingang 3	control input
Eingang 4	tachometer input

housing

material	Kunststoffgehäuse mit 28 Schraubklemmen, geeignet für Hut-schinenmontage DIN EN 50022-35
ultrasonic transducer	polyurethane foam, epoxy resin with glass contents
class of protection to EN 60529	IP 20
operating temperature	-20°C to +70°C non-condensing
storage temperature	-20°C to +70°C
weight	200 g

Technical Features/Characteristics

controls	3 push-buttons
scope for settings	at the evaluator with terminal programme via serial interface
synchronization	yes
multiplex	no
indicators	2 x LED yellow: switch status, 2 x LED red: operating status
particularities	unklar