



extract from our online catalogue:

mic-101/IU/HV/M30/ K2 R1


current to: 2026-09-22

mic-101/IU/HV/M30/ K2 R1

scale drawing



detection zone



Successor model available

please inquire

1 x analogue 4-20 mA + 0-10 V

2,000 mm

design

cylindrical M30

operating mode

analogue distance measurements

particularities

archive sensor
cable connection

Ultrasonic-Specific

means of measurement

echo propagation time measurement

transducer frequency

200 kHz

blind zone

200 mm

operating range

1,300 mm

max. range

2,000 mm

resolution

0,18 mm

reproducibility

± 0,15 %

accuracy

± 1 % (temperature drift internally compensated)

Electrical Data

operating voltage U_B

9 - 30 V d.c., reverse polarity protection

voltage ripple

± 10 %

no-load current consumption

≤ 70 mA

type of connection

2 m PVC cable, 4 × 0,34 mm²

outputs

output 1	analogue output current: 4-20 mA / voltage: 0-10 V (at $U_B \geq 15$ V), short-circuit-proof switchable rising/falling
response delay	110 ms
delay prior to availability	< 1,500 ms

Inputs

input 1	com input synchronisation input
---------	------------------------------------

housing

material	brass sleeve, nickel-plated, plastic parts, PBT, TPU
ultrasonic transducer	polyurethane foam, epoxy resin with glass contents
class of protection to EN 60529	IP 65
operating temperature	-20°C to +70°C
storage temperature	-40°C to +85°C
weight	260 g
further versions	mic-101/IU/HV/M30/ K10 R1
further versions	different cable length

Technical Features/Characteristics

temperature compensation	yes
controls	2 push-buttons + LED display (TouchControl) com input
scope for settings	Teach-in and numeric configuration via TouchControl LCA-2 with LinkControl
synchronization	yes
multiplex	yes
indicators	2 x three-colour LED