microsonic



extract from our online catalogue:

# *mic-25/D/HV/M30 R1*

current to: 2026-11-19

microsonic GmbH / Phoenixseestraße 7 / 44263 Dortmund / Germany / **T** +49 231 975151-0 / **F** +49 231 975151-51 / **E** info@microsonic.de
microsonic® ist eine eingetragene Marke der microsonic GmbH. Alle Rechte vorbehalten. Änderungen vorbehalten.

Archivsensor

# mic-25/D/HV/M30 R1

## scale drawing




## detection zone




| Successor model available | mic+25/D/TC |
|---|---|
| 1 x pnp | 350 mm |
| design | cylindrical M30 |
| operating mode | proximity switch/reflective mode<br>reflective barrier<br>window mode |
| particularities | archive sensor |

## Ultrasonic-Specific

| | |
|---|---|
| means of measurement | echo propagation time measurement |
| transducer frequency | 320 kHz |
| blind zone | 30 mm |
| operating range | 250 mm |
| max. range | 350 mm |
| resolution | 0.18 mm |
| reproducibility | ± 0.15 % |
| accuracy | ± 1 % (temperature drift internally compensated) |

## Electrical Data

| | |
|---|---|
| operating voltage $U_B$ | 9 - 30 V d.c., reverse polarity protection |
| voltage ripple | ± 10 % |
| no-load current consumption | ≤ 70 mA |
| type of connection | 5-pin M12 initiator plug |

## Outputs

| | |
|---|---|
| output 1 | switching output<br>pnp: $I_{max}$ = 200 mA ($U_B$-2V)<br>NOC/NCC adjustable, short-circuit-proof |
| switching hysteresis | 3 mm |
| switching frequency | 11 Hz |
| response delay | 50 ms |
| delay prior to availability | < 1,500 ms |

## Inputs

| | |
|---|---|
| input 1 | com input<br>synchronisation input |

## Housing

| | |
|---|---|
| material | brass sleeve, nickel-plated, plastic parts, PBT |
| ultrasonic transducer | polyurethane foam, epoxy resin with glass contents |
| class of protection to EN 60529 | IP 65 |
| operating temperature | -20°C to +70°C |
| storage temperature | -40°C to +85°C |
| weight | 260 g |
| further versions | mic-25/D/HV/M30E R1<br>mic-25/D/HV/M30/ K6 R1 |
| further versions | stainless steel<br>cable connection (on request) |

## Technical Features/Characteristics

| | |
|---|---|
| temperature compensation | yes |
| controls | 2 push-buttons + LED display (TouchControl)<br/>com input |
| scope for settings | Teach-in and numeric configuration via TouchControl<br>LCA-2 with LinkControl |
| synchronization | yes |
| multiplex | yes |
| indicators | 2 x three-colour LED |

## Accessories

| | |
|---|---|
| deployable accessory | KST5A-2/M12<br>KST5A-5/M12<br>KST5G-2/M12<br>KST5G-5/M12 |

## *pin assignment*

