




extract from our online catalogue:

## ***pico-usp 25/CD/HV/M18***


current to: 2026-09-22

# pico-usp 25/CD/HV/M18

## scale drawing



## detection zone



Successor model available

please inquire

1 x pnp

350 mm

design

cylindrical M18

operating mode

analogue distance measurements

particularities

digital signal proportional to distance

## Ultrasonic-Specific

means of measurement

echo propagation time measurement

transducer frequency

320 kHz

blind zone

30 mm

operating range

250 mm

max. range

350 mm

resolution

0.36 mm

reproducibility

± 0.15 %

accuracy

temperature drift 0.17 %/K

## Electrical Data

operating voltage  $U_B$

10 - 30 V d.c., reverse polarity protection

voltage ripple

± 10 %

no-load current consumption

≤ 30 mA

type of connection

4-pin M12 initiator plug

## outputs

output 1

PWM output  
pnp:  $I_{max} = 500 \text{ mA}$  ( $U_B - 2V$ )

response delay

24 ms

delay prior to availability

< 300 ms

## Inputs

input 1

enable-input

## housing

|                                 |                                                    |
|---------------------------------|----------------------------------------------------|
| material                        | brass sleeve, nickel-plated, plastic parts, PBT    |
| ultrasonic transducer           | polyurethane foam, epoxy resin with glass contents |
| class of protection to EN 60529 | IP 65                                              |
| operating temperature           | -20°C to +70°C                                     |
| storage temperature             | -40°C to +85°C                                     |
| weight                          | 60 g                                               |

## Technical Features/Characteristics

|                          |               |
|--------------------------|---------------|
| temperature compensation | no            |
| controls                 | not necessary |
| scope for settings       | not necessary |
| synchronization          | no            |
| multiplex                | no            |
| indicators               | no            |

## Accessories

|                      |                                                                                                     |
|----------------------|-----------------------------------------------------------------------------------------------------|
| deployable accessory | KST4A-2/M12<br>KST4A-5/M12<br>KST4G-2/M12<br>KST4G-5/M12<br>BF-18<br>UF-90/M18<br>Aufschraubdom M18 |
|----------------------|-----------------------------------------------------------------------------------------------------|

## pin assignment

