Controllo qualità



Settori di applicazione

Alimentare e farmaceutico

Logistica

Imballaggio

In packaging machines, quality control is crucial to monitor the flow of bottles at filling systems, for example, and prevent jams. When detecting transparent objects in production processes, reliability and jam monitoring are essential. Ultrasonic sensors detect objects—such as glass bottles, transparent PET containers, or cans—contact-free and precisely, without optical interference.

Depending on the object size and measurement range, four sensor families with different sensing ranges are available:

- **pico+ with M18 threaded sleeve:** 20 mm to 1.3 m measurement range for small packaging units or beverage bottles,
- **lpc+ with M18 threaded sleeve:** 20 mm to 1.3 m measurement range with 2 output stages,
- **zws in a cubic miniature housing:** 20 mm to 1 m measurement range for small objects and packaging units in fast production processes, and
- **pms in Hygienic Design:** 20 mm to 1.3 m measurement range for use in food or pharmaceutical products.

SENSORI PER QUESTO SETTORE DI APPLICAZIONE



pico+

housing: M18 all-metal sleeve
detection ranges: 250 mm, 350 mm, 600 mm and 1,300 mm
outputs: 1x Push-Pull, 4-20 mA or 0...



lpc+

housing: M18 all-metal sleeve
detection ranges: 250 mm, 350 mm, 600 mm and 1,300 mm
outputs: 2x Push-Pull, 1x Push-Pull...



zws

housing: miniature cubic housing
detection ranges: 150 mm, 240 mm, 250 mm, 350 mm and 700 mm
outputs: 1x pnp or npn, 4-20 mA or ...



pms

La famiglia di sensori con design igienico si distingue per la sua struttura in acciaio inossidabile priva di fessure e spigoli dove possa...