



Uittreksel uit onze online-catalogus:

LCA-2 Koffer

Stand: 2026-09-02

LCA-2 Koffer

Bedrijfsmodus	toebehoren
Hoogtepunten	incl. adapterkabel en 24V voeding

Elektrische gegevens

Bedrijfsspanning U_B	12 V tot 30 V DC, ompoolbeveiligd
Restrimpel	$\pm 10 \%$
Onbelaste stroomopname	$\leq 25 \text{ mA}$
Aansluitmethode	4-polige, ronde M12-connector

Ingangen

Ingang 1	com-ingang
----------	------------

Behuizing

Materiaal	ABS
Beschermingsklasse volgens EN 60529	IP 20
Bedrijfstemperatuur	+5° C tot +60° C
Opslagtemperatuur	-40° C tot +85° C
Gewicht	1.700 g

Uitrusting/Bijzonderheden

Instelelementen	4 toetsen + LED-aanwijzing (TouchControl)
Indicatoren	LED-aanwijzing met 3 cijfers

Toebehoren

Inzetbare accessoires	Set voor de comfortabele instelling van veel microsonic-sensor-families. Contents: - LCA-2 - Adaptor for sensors with cable connection (lcs) incl. cable clamps - Adapter for power supply incl. cable clamps - Power supply 90-240VAC/24VDC, 625 mA, with 2,5 m cable - four exchangeable AC-plugs for use in Europe, USA, Great Britain and Australia - USB - cable A-plug to B-plug - USB-Stick with LinkControl software - Manual (German / English)
-----------------------	---