# Контроль уровня



Возможен контроль уровня заполнения емкости от нескольких миллиметров до 8 м. Применяются ультразвуковые датчики с одним или двумя выходами для определения минимального / максимального уровня, или с аналоговым выходом 0-10 В и 4-20 мА . Химически устойчивое исполнение также доступно для ультразвуковых датчиков семейств pico+TF, crm+ или hps+ .

### *Области применения*

- Printing and Paper
- Food and Pharmaceuticals
- Logistics
- Packaging

## ДАТЧИКИ ДЛЯ ЭТОЙ ОБЛАСТИ ПРИМЕНЕНИЯ



### *mic+*
**housing:** M30 sleeve with digital display
**detection ranges:** 250 mm, 350 mm, 1,300 mm, 3,400 and 6,000 mm ...



### *pico+TF*
**housing:** M22 sleeve in PVDF
**detection ranges:** 250 mm, 350 mm, 600 mm and 1,300 mm
**outputs:** 1x Push-Pull, 4-20 mA or 0...



### *crm+*
**housing:** M30 sleeve in stainless steel
**detection ranges:** 250 mm, 350 mm, 1,300 mm, 3,400 and 6,000 mm
**outputs:** 1x Push-Pull, 2x pnp, 4-20...



### *hps+*
**housing:** PVDF or stainless steel housing with PTFE film
**detection ranges:** 250 mm, 350 mm, 1,300 mm and 3,400...



### *pms*
**housing:** stainless steel housing with PTFE film
**detection ranges:** 250 mm, 350 mm, 600 mm and 1,300 mm...